


Triple-IGU Features/Benefits Comparison

Warmer in Winter


The winter nighttime U-Value (insulating value) of a **Sungate 400 (3)(5)** glass unit is **52%** better than standard clear insulating glass.

- Lower U-values mean higher performance
- Reduces furnace heat loss
- Helps reduce heating energy costs

Standard Clear Insulating Glass





Sungate 400 (3)(5) Insulating Glass



Warmer During Winter Daylight

The total solar energy transmitted through **Sungate 400 (3)(5)** glass is only **10%** less than that transmitted by standard clear insulating glass.



- Higher SHGC numbers mean more solar heat gain
- Helps keep interiors warmer
- Helps reduce heating energy costs



Transmits Visible Light/Appearance

Insulating units with **Sungate 400 (3)(5)** transmit about **93%** of the visible light as standard clear insulating glass.



- Interior light from the sun not reduced dramatically versus clear glass
- Provides exterior appearance similar to clear glass



Fading Factors

While **Sungate 400 (3)(5)** glass blocks **84%** of damaging UV energy, it also blocks other contributors to fading – in all, **21%** better than standard clear insulating glass.

- Helps protect interior furnishings, fabrics and carpets from fading



Note: Tdw-ISO represents potential fading damage caused by both UV and visible light. It is considered by the U.S. Department of Energy and the International Standards Organization (ISO) to be a more accurate barometer of fade resistance than UV transmittance alone. All comparisons are center of glass based on an insulating unit containing 1 3/8" (overall dimension) insulating units with three 1/8" (3mm) glass lites and two 1/2" (12mm) air-filled spaces for the Sungate® 400 insulating glass. Actual glass performance may differ due to glass thickness, gas fill and glass to frame ratio.

Solar Heat Gain Coefficient (SHGC) represents the solar heat gain through the glass relative to the incident solar radiation. It is equal to 86% of the shading coefficient.

Figures may vary due to manufacturing tolerances. All tabulated data are based on the National Fenestration Rating Council (NFRC) methodology, using the Lawrence Berkeley National Laboratory's Window 6.3 software.



PPG customers use our products to manufacture Energy Star compliant windows, doors and skylights.



PPG Industries, Inc.
Glass Business & Discovery Center
400 Guys Run Road, Cheswick, PA 15024
Phone: 1-888-PPG-GLAS